



SPRAYLAC (1012-005)

Spraylac is an aerosol applied pre-catalysed lacquer that is suitable for the repair of scratches and surface defects on coated and uncoated timber.

Product Advantages

- Fast drying
- Easy to apply straight from the can

Typical Applications

Repair of small scratches and surface defects

Colour: Clear

Gloss Level: Satin (30%) & Semi Gloss (60%)

Application Methods:

Apply a light even coat with can held approximately 30 cm from the article being coated. Do not apply excessive film builds.

Spraylac may be applied over a wide range of coatings, however a small test area should be prepared before coating the whole article. Do not coat large areas with aerosol products as the coating may dry unevenly causing the gloss level to appear patchy.

Shelf Life: 24 months

Packaging: 300 gram aerosol can

Health & Safety

Before handling, refer to the Material Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated MSDS and packaging label before using this product.

Mirotone Pty Ltd Australia (Head Office)
ABN 40 000 041 136
21 Marigold Street,
Revesby NSW 2212 Australia
P +61 2 9795 3700 F +61 2 9771 3601
sales@mirotone.com.au

Mirotone (NZ) Ltd New Zealand (Head Office)
32 Cryers Road,
Auckland, 1730, New Zealand
P +64 9 272 2730 F +64 9 272 2733
information@mirotone.co.nz

Mirotone (Thailand) Co., Ltd
83 Moo 4, Poochaosamingprai Rd,
Samrong Klang, Prapradaeng,
Samutprakam, 10130, Thailand
P +66 2 754 4451 F +66 2 754 4450

www.mirotone.com